

11KV HEAT SHRINKABLE CABLE ACCESSORIES

Technical Data

Property	Typical data
Ac withstand(under rain)	45KV/1min
Ac withstand(without rain)	45KV/1min
Impulse withstand	±105KV/10times
Dc withstand	-52KV/15min
Ac withstand	35KV/4h
Partial discharge test	≤10Pc(1.73U ₀)



Dimension(mm)

Description of goods	Specification	Size of Conductor (mm ²)	Description of goods	Specification	Size of Conductor (mm ²)
Single core "XLPE" indoor termination kit	NSY-11/1.1	25-50	3-cores "XLPE" indoor termination kit	NSY-11/3.1	25-50
	NSY-11/1.2	70-120		NSY-11/3.2	70-120
	NSY-11/1.3	150-240		NSY-11/3.3	150-240
	NSY-11/1.4	300-500		NSY-11/3.4	300-500
Single core "XLPE" outdoor termination kit	WSY-11/1.1	25-50	3-cores "XLPE" outdoor termination kit	WSY-11/3.1	25-50
	WSY-11/1.2	70-120		WSY-11/3.2	70-120
	WSY-11/1.3	150-240		WSY-11/3.3	150-240
	WSY-11/1.4	300-500		WSY-11/3.4	300-500
Single core "XLPE" straight through joint	JSY-11/1.1	25-50	3-cores "XLPE" straight through joint	JSY-11/3.1	25-50
	JSY-11/1.2	70-120		JSY-11/3.2	70-120
	JSY-11/1.3	150-240		JSY-11/3.3	150-240
	JSY-11/1.4	300-500		JSY-11/3.4	300-500
3-cores "PILC" outdoor termination kit	NSZ-11/3.1	25-50	3-cores "PILC" straight through joint	JSZ-11/3.1	25-50
	NSZ-11/3.2	70-120		JSZ-11/3.2	70-120
	NSZ-11/3.3	150-240		JSZ-11/3.3	150-240
	NSZ-11/3.4	300-500		JSZ-11/3.4	300-500
3-cores "PILC" outdoor termination kit	WSZ-11/3.1	25-50			
	WSZ-11/3.2	70-120			
	WSZ-11/3.3	150-240			
	WSZ-11/3.4	300-500			